



NATIONAL PETROLEUM COMPANY- NPC

AMMAN JORDAN
TENDER NO. 26/2021/S
Schedule of specifications and prices

SUBJECT: NEW ELECTRIC HYDRUALIC POWER UNIT (SKIDED)

Risha Stone

Item No.	DESCRIPTIONS	UNIT	QTY	W/O CUSTOMS & TAXES	
				C & F : QAI <i>Rish</i>	
				Unit price	Total Price
1	EXPLOSION PROOF & CONTINOUS DUTY ELECTRIC MOTOR (100 HP , 600 V , 3PH , 1800 RPM).	SET	1		
	HEAVY DUTY GEAR PUMP WITH MAX OPERATING PRESSURE 2500 PSI PRESSURE IS 2500 PSI @ 80 GPM FLOW RATE.				
	EXPLOSION PROOF STARTER (CAST ALUMINUM SEALD) WITH ALL ELECTRIC PARTS (CONTACTOR , OVERLOAD.....ETC)				
	HYDRUALIC TANK STEEL CONSTRUCTION FULLY WELDED WITH (135 GPM) @ OPERATING TEMP (100-150 F) INCLUDE:- 1- FILTERED BREATHER. 2- TOP ACCESS HATCH. 3- INLET & OUTLET PLUG 2". 4- RETURN FILTER WITH SIGHT GAGES (DIRTY ELEMENT, NO ELEMENT, OPERATION OK) & FULL FLOW RETURN LINE.				
	OIL COOLER (OIL /AIR TYBE) WITH OPERATING PRESSURE (500 PSI) & MAX FLOW RATE (80 GPM) & OVERSIZED FOR HOT CLIMATES.				
	FRAME (ASTM-A36) STEEL CONSTRUCTION & FULLY WELDED BELLY PAN INCLUDE:- 1- LEFT EYES ON TOP. 2- FULLY LENGTH FORKLIFT TUBES. 3- BASKET WITH COVER FOR HOSES ON TOP. DRAIN PLUG 2"				
	CONTROL PANEL INCLUDE:- 1- DIRECTIONAL CONTROL WORK SECTION TO LEFT RISING WINCH WITH FLOW VALVE (PORT 1"). 2- DIRECTIONAL CONTROL WORK SECTION TO RIGHT RISING WINCH WITH FLOW VALVE (PORT 1"). 3- DIRECTIONAL CONTROL WORK SECTION (KICK CYLINDER) WITH (RELIEF CARTRIDGE SET 1000 PSI) (PORT 1/4"). 4- GAGES (OUTPUT PRESSURE (0-3000 PSI) , TANK TEMP , TANK LEVEL , MOTOR TEMP , HOUR METER , LOW OIL LEVEL/SHUTOFF , REMOTE START/STOP , FILTERATION STATES)				
	RELEVE VALVE ADJUSTABLE WITH FACTORY PRESSURE SET (2500 PSI)				
	(4) PRESSURE CAP 1" WITH FEMALE QUICK DISCONNECT PRESSURE WITH DUST PLUG & CAP TO DIRECTIONAL CONTROL WORK SECTION TO LEFT & RIGHT RISING WINCH WITH				
	(1) PRESSURE CAP 1" DIRECT FROM PUMP + (1) RETURN CAP 1" WITH FEMALE QUICK DISCONNECT PRESSURE WITH DUST PLUG & CAP.				
	(1) PRESSURE CAP 1/4" WITH FEMALE QUICK DISCONNECT PRESSURE WITH DUST PLUG & CAP + (1) RETURN CAP 1/4" WITH FEMALE QUICK DISCONNECT WITH DUST PLUG & CAP PRESSURE CONNECT WITH THE DIRECTIONAL CONTROL WORK SECTION (KICK CYLINDER) .				
(1) RETURN CAP 3/4" WITH FEMALE QUICK DISCONNECT PRESSURE WITH DUST PLUG & CAP.					
2	MALE QUICK DISCONNECT PRESSURE SIZE (1") WITH DUST PLUG & CAP	EA	12		
3	FEMALE QUICK DISCONNECT PRESSURE SIZE (1")WITH DUST PLUG & CAP	EA	6		
4	MALE QUICK DISCONNECT PRESSURE SIZE (1/4") WITH DUST PLUG & CAP	EA	4		
5	FEMALE QUICK DISCONNECT PRESSURE SIZE (1/4") WITH DUST PLUG & CAP	EA	4		
6	MALE QUICK DISCONNECT PRESSURE SIZE (3/4") WITH DUST PLUG & CAP	EA	2		
7	FEMALE QUICK DISCONNECT PRESSURE SIZE (3/4") WITH DUST PLUG & CAP	EA	2		
				TOTAL	
CURRENCY:		MODE OF PAYMENT :			
DELIVERY PERIOD :		PLACE OF DELIVERY:			
VALIDITY :		BANK GUARANTEE :			
MANUFACTURER:		DATE OF MANUFACTURING :		ORIGIN OF GOODS :	
SPECIAL CONDITIONS:					
NOTES:					
THE ACCEPT PRODUCTS MUST BE OEM					
ALL COLUMNS AND BLANK MUST BE FILLED IN AND IT'S THE NPC CHOICE TO CHOOSE THE PRICE WHICH SUITS IT'S REQUIRMENT					
ORIGINATOR: ENG. ALI ALNAIMI		SIGNATURE 		DATE:-27/06/2021	
HEAD OF DIVISION: ENG. MAHMOUD ALROUSAN		SIGNATURE		DATE:-27/06/2021	
DEPARTMENT MANAGER: ENG. MUWAFIQ KHASAWNH		SIGNATURE 		DATE:-27/06/2021	



Handwritten signature and date