



NATIONAL PETROLEUM COMPANY- NPC

AMMAN JORDAN

TENDER NO. 22/2021/C

Schedule of specifications and prices

SUBJECT: MUD CHEMICALS

Item No.	DESCRIPTION	UNIT	QTY	W/O CUSTOMS & TAXES	
				C & F: <i>Risha Stones</i>	
				Unit price	Total Price
1-1	PAC LV	SX	1050		
1-2	PAC HV	SX	30		
1-3	CMC LV	SX	3000		
1-4	CMC HV	SX	1800		
1-5	STARCH	SX	30		
1-6	FCL	SX	300		
1-7	SODIUM BICARBONATE	SX	60		
1-8	BENEX (MON-EX)	SX	150		
1-9	XCD	SX	210		
1-10	SUPER SEAL	SX	360		
1-11	MICA	SX	750		
					TOTAL

CURRENCY:	MODE OF PAYMENT :	
DELIVERY PERIOD :	PLACE OF DELIVERY:	
VALIDITY :	BANK GUARANTEE :	
MANUFACTURER:	ORIGIN OF GOODS :	
SPECIAL CONDITIONS:		
NOTES:		
ALL COLUMNS AND BLANK MUST BE FILLED IN AND IT'S THE NPC CHOICE TO CHOOSE THE PRICE WHICH SUITS IT'S REQUIRMENT		
ORIGINATOR: SAMER NABIL	SIGNATURE <i>Samer</i>	DATE: 05/05/2021
HEAD OF DIVISION: ZAIDOUN SHAKHATEREH	SIGNATURE <i>Zaidoun</i>	DATE: 05/05/2021
DEPARTMENT MANAGER: <i>محمد</i>	SIGNATURE <i>محمد</i>	DATE: 05/05/2021



Tender 22/2021/C

C & F
Risha Stone

Item No.	DESCRIPTIONS	UNIT
1-	STARCH: PRE-GELATINIZED STARCH, POWDER OR IN GRANULAR FORM (1 TO 2 MM MAX. DIN) TO BE USED AS A WATER LOSS REDUCER FOR ALL WATER BASED MUD (FRESH OR SATURATED SALT WATER SYSTEM) FULLY CONFORMED TO API 13-A SPECIFICATION. PACKED IN 25 KG PER SAX, EACH TO BE OF 5-PLY PAPER BAGS, CONSTRUCTION WITH AT LEAST ONE PLY WATERPROOFED LOTS OF 40 BG TO BE, STRAPPED AND WRAPPED ON PALLETS CONSTRUCTED OF HARDWOOD TWO-WAY ENTRY EXPORT TYPE. POLY ETHYLENE COVER.	SX
2-	BENTONITE: POWDER SODIUM MONTMORILLONITE MINIMUM YIELD (16.00) CU.M/TONNE OF 15 CP FILTRATE 15CC MAX IN CONSTRATION OF 75 GR OF BENTONITE IN 100 ML OF DISTELED WATER, FULLY CONFORMED TO API 13-A SPECIFICATION. . PACKED IN 25KG BAGS, EACH TO BE OF 5-PLY PAPER BAGS CONSTRUCTION WITH AT LEAST ONE PLY WATERPROOFED LOTS OF 40 BG TO BE STRAPPED AND WRAPPED ON PALLETS CONSTRUCTED OF HARDWOOD TWO-WAY ENTRY EXPORT TYPE. POLYETHELN COVER.	SX
3-	CEPACK-LV: POLYANIONIC CELLULOSE OFF WHITE POWDER (9-18) LBS/CU. FT BULK DENSITY RANGE, STABLE AT MINIMUM 350 F DEY. TEMP. PACKED IN 25KG (EACH TO BE OF 5-PLY PAPER BAGS). CONSTRUCTION WITH INNER AND OUTER POLYTHENE COATED LOTS OF 40 BG TO BE STRUPPED AND WRAPPED ON PALLETS CONSTRUCTED OF HARD WOOD TWO-WAY ENTRY EXPORT TYPE POLYETHYLENE COVER.	SX
4-	CEPACK-HV: POLYANIONIC CEILULOSE OFF WHITE POWDER (9-18) LBS/CU.FT BULK DENSITY RANGE, STABLE AT MINIMUM 350F DEG, TEMP, PACKED IN 25KG, EACH TO BE 5-PLY PAPER BAGS CONSTRUCTION WITH INNER AND OUTER POLYTHENE COATED LOTS OF 40 BG TO BE STRAPPED AND WRAPPED ON PALLETS CONSTRUCTED OF HARDWOOD TWO-WAY ENTRY EXPORT TYPE POLY ETHYLENE COVER.	SX
1-	CMC HI-VIS: TECHNICAL GRADE HIGH VISCOSITY, CARBOXIMETHYCELLUSE IN GRANULAR FORM (1 TO 3 MM MAX. DIA) FOR FILTRATION AND VISCOSITY CONTROL. FULLY CONFORMED TO API 13-A SPECIFICATION. PACKED IN POLYPROPY LENE BAGS CONTAINING 25KG LOTS OF 40 BAGS TO BE STRAPPED AND WARPED ON PALLETS 2 WAY ENTRY EXPORT TYPE, WITH POLYETHELENE COVER.	SX
2-	CMC LO-VIS: TECHNICAL GRADE LOW VISCOSITY CARBOXIMETHLYCELLUSE IN GRANULAR FORM (1 TO 3 MM MAX DIE) FOR FILTRATION AND VISCOSITY CONTROL, FULLY CONFORMED TO API 13-A SPECIFICATION PACKED IN POLYPROPLENE BAGS CONTAINING 25KG LOTS OF 40 BAGS TO BE STRAPPED AND WRAPPED ON PALLETS 2-WAY ENTRY EXPORT TYPE, WITH POLYETHLENE COVER.	SX
3-	MICA-COARSE: MICA FLAKES, FINE GRADE, NON ABRASIVE SELECTED FROM MINERAL MICA (MUSCOVITE) USED FOR PREVENTION OF LOST CIRCULATION AND ALLOWING FULL USE OF 20-MESH SHALE SHAKER, PACKE IN PAPER BAGS. CONTAINING 25 KG BAGS TO BE OF 5-PLY INCLUDING ONE POLYETHELENE LINER, LOTS OF 40 BAGS POLYETHELENE COVER TO BE STRAPPED AND RAPPED ON PALLETS OF HARD WOOD TWO-WAY ENTRY EXPORT TYPE POLYETHELENE COVER	SX
4-	BENTONITE EXTENDER (BENEX) HIGH MOLECULAR WEIGHT POLYMER PACKED IN POLYPROPY LENE, BAGS CONTAINING 2 LB, NETT EXPORT QUANTITY TO BE STRAPPED AND WRAPPED ON CORTONS OR BOXES.	SX
3-	SODIUM BICARBONATE WHITE FORM OF SPEC.GRAVITY OF 2.16 PACKED IN POLYPROPYLINE BAGS. CONTAINING 25 KG BAGS LOTS OF 40 BAGS ON PALLETS POLYATHELENE COVER TO BE STRAPPED AND RAPPED ON PALLETS OF HARD WOOD TWO -WAY ENTRY EXPORT TYPE POLYETHELENE COVER. NaCO3	SX
1-	XCD-POLYMER: XANTHAN GUM PRIMARY VISCIFYING POLYMER POWDER 52.5 LB/CU.FT BULK DENSITY RANGE STABLE AT MINIMUM 300F DEG. TEMP. PACKED IN 25KG, EACH TO BE OF 5-PLY PAPER BAGS CONSTRUCTION WITH INNER AND OUTER POLYTHENE COATED LOTS OF 40 BG TO BE STRAPPED AND WRAPPED ON PALLETS CONSTRUCTED OF HARDWOOD TWO-WAY ENTRY EXPORT TYPE. POLY ETHYLENE COVER.	SX

