## NATIONAL PETROLEUM COMPANY- NPC AMMAN JORDAN TENDER NO. Schedule of specifications and prices

## SUBJECT: CHOKE MANIFOLD

|             |   | C11- |     |   |                     |  |
|-------------|---|------|-----|---|---------------------|--|
| Item<br>No. | 20-20-cg  | UNIT | QTY | W/O CUSTOMS & TAXES C & F : AQABA PORT THE TO RISHA WAREHOUSE |                     |  |
|             |   |      |     |   |                     |  |
|             | CHOKE AND KILL WELL CONTROL MANIFOLD FOR SOUR GAS WELL DRILLING AS API-6A SPECIFICATION, WITH FOLLOWING SPECIFICATIONS: | SET  | 1   | Unit price  | Total Price         |  |
|             | WORKING PRESSURE : 5000 PSI   |      |     |   |                     |  |
|             | PERFORMANCE REQUIRED: PR-1  |      |     |   |                     |  |
|             | PRODUCT SPICIFICATION LEVEL : PSL-3   |      |     |   |                     |  |
|             | MATERIAL CLASS: EE  |      |     |   |                     |  |
|             | TEMPRATURE RATING: U  |      |     |   |                     |  |
| 1-          | TRIM CODE: S-24   |      |     |   |                     |  |
|             | VALVES TYPE: GATE VALVES  |      |     | 8 - 10 A - 7  | <u> </u>            |  |
| ŀ           | ONE 2" ADJUSTABLE CHOKE   |      |     |   |                     |  |
| - 1         | ONE 2" FIXED CHOKE  |      |     |   |                     |  |
| - Je        | ONE PRESSURE GUAGE AFTER MAIN INLET VALVE   |      |     |   | 46)<br>00 - 12 Ho B |  |
|             | ONE PRESSURE GUAGE ON OUTLET VALVE  |      |     |   |                     |  |
|             | MAIN INLET VALVE 4" FLANGED ( R-39 )  |      |     |   |                     |  |
| - 1         | ALL INNER VALVES 2" FLANGED   |      |     |   |                     |  |
|             | THREE OUTLIT LINES  |      |     |   |                     |  |
| 1 A         | DAPTER 2" FLANGED X 2" HUMMER UNION FEMALE THREAD FIG 1502  | EA   | +   |   |                     |  |
| 2 2         | " PLUG VALVE HUMMER UNION MALE X FEMALE   | EA   | 3   |   |                     |  |
|             | " SWIVEL JOINT STYLE 50 FIG 1502 MALE X FEMALE  | EA   | 1   |   |                     |  |
| R           | ING GASKET R-39 STAINLESS STEEL   | EA   | 4   |   |                     |  |
|             | EAN 16/64 FOR ABOVE FIXED CHOKE   | EA   | +   |   |                     |  |
| В           | EAN 24/64 FOR ABOVE FIXED CHOKE   | EA   |     |   |                     |  |
| B           | EAN 32/64 FOR ABOVE FIXED CHOKE   | EA   | 1   |   |                     |  |
| В           | EAN 48/64 FOR ABOVE FIXED CHOKE   | EA   | 1   |   |                     |  |
| В           | EAN 64/64 FOR ABOVE FIXED CHOKE   | EA   | 1   |   |                     |  |
|             |   |      |     | TOTAL   |                     |  |

| CURRENCY:  | MODE OF PAYMENT :   |  |  |  |  |  |
|--|---|--|--|--|--|--|
| DELIVERY PERIOD :  | PLACE OF DELIVERY:  |  |  |  |  |  |
| VALIDITY:  | BANK GUARANTEE :  |  |  |  |  |  |
| MANUFACTURER:  | ORIGIN OF GOODS:  |  |  |  |  |  |
| DATE OF MANUFACTURING:   | A TO THE STATE OF |  |  |  |  |  |
| SPECIAL CONDITIONS:  |   |  |  |  |  |  |
| OTES:  |   |  |  |  |  |  |
| THE PRODUCT SHOULD BE BRAND NEW AND PRESSURED TESTED.            | <del></del>   |  |  |  |  |  |
| THE OFFER SHOULD CONTAIN ALL API CERTIFICATION.                  |   |  |  |  |  |  |
| ALL VALVES SHOULD BE ASSEMBLED AND FIXED ON SKID WITH 4 NOS LIF  | TING PAD FYFS   |  |  |  |  |  |
| THE CHOKE CONFIGRATION SHOULD BE AS API-16C SPECIFICATION        |   |  |  |  |  |  |
| THE ACCEPT PRODUCTS MUST BE OF USA, SINGAPORE, CANADIAN, EUROP.  | EAN ORIGIN AND MANUFACTUR   |  |  |  |  |  |
| ALL COLUMS AND BLANK MUST BE FILLED IN AND IT'S THE NPC CHOICE T |   |  |  |  |  |  |
| ORIGINATOR: Eng. Osama Almaani                                   | SIGNATURE DATE: 20/9/2020   |  |  |  |  |  |
| HEAD OF DIVISION: Frederich Gunk Wester 4                        |   |  |  |  |  |  |
| DEPARTMENT MANAGER:  | SIGNATURE DATE: 2 7 20  |  |  |  |  |  |
| 1/2_   |   |  |  |  |  |  |

## NATIONAL PETROLEUM COMPANY- NPC

AMMAN JORDAN
TENDER NO.
Schedule of specifications and prices

## SUBJECT: CHOKE & KILL HOSE

| <u> </u>      | OUP:II   |                |              |      | Ci  | r           |  |  |
|---------------|--|----------------|--------------|------|---|-------------|--|--|
| Item<br>No.   | DESCRIPTIONS   |                | UNIT         | QTY  | W/O CUSTOMS & TAXES C & F : AQABA PORT THE TO RISHA WAREHOUSE |             |  |  |
|               |  |                |              |      | Unit price  | Total Price |  |  |
| . Vi          | FLEXIBLE CHOKE AND KILL HOSE FOR SOUR GAS WELL AS API 16C SPRCIFICATION WITH THE FOLLOWING:                              |                |              |      |   |             |  |  |
|               | WORKING PRESSURE: 5000 PSI.  OD" 6.25"  ID: 4"   |                |              |      |   | );          |  |  |
|               |  |                |              |      |   |             |  |  |
|               |  |                |              |      |   | S           |  |  |
|               | GRADE: D   |                | }            | 1    |   |             |  |  |
| 1-            | LENGTH: 60'  |                | EA           |      |   |             |  |  |
|               | COUPLINGS: 4-1/16" FLANGE END BOTH SIDES.  EXTERNAL ARMORED LAYER: STAINLESS STEEL.  OPERATING TEMPRATURE: -18 TO +121 C |                |              |      | ĺ   |             |  |  |
|               |  |                |              |      |   |             |  |  |
|               |  |                |              |      |   | · · ·       |  |  |
|               | WITH HOSE LIFTING EYES.  |                | -            | }    | -   |             |  |  |
|               |  |                |              |      |   |             |  |  |
| 77.65         |  | <u>-</u>       |              |      |   |             |  |  |
|               |  |                | <u> </u>     |      | TOTAL   | 55          |  |  |
| URRE:         | NCY:   | wong or        |              |      |   |             |  |  |
| MODE (        |  | MODE OF PAYM   |              |      |   |             |  |  |
| ALIDITY .     |  |                | <del>-</del> |      | <del></del>   |             |  |  |
| MANUFACTURED. |  |                |              |      | <del></del>   |             |  |  |
|               | F MANUFACTURING:   | ORIGIN OF GOOD | DS :         |      |   |             |  |  |
|               | L CONDITIONS:  |                | - NS         | - 3  |   |             |  |  |
| OTES:         |  |                | <u> </u>     | . 19 | - 23/3  |             |  |  |
| HE DD/        | DDUCT SHOULD BE BRAND NEW AND PRESSURED TESTED AT 10000 PS   |                |              |      |   |             |  |  |

ORIGINATOR: Eng. Osama Almaani

HEAD OF DIVISION:

DATE: 20/9/2020

DATE: 3/4 CC 2

DEPARTMENT MANAGER:

SIGNATURE

DATE: 4/1/20 2 CC

ALL COLUMS AND BLANK MUST BE FILLED IN AND IT'S THE NPC CHOICE TO CHOOSE THE PRICE WHICH SUITS IT'S REQUIRMENT

THE ACCEPT PRODUCTS MUST BE OF USA, SINGAPORE, CANADIAN, EUROPEAN ORIGIN AND MANUFACTUR

THE OFFER SHOULD CONTAIN ALL API CERTIFICATION.